

Carbon Monoxide CiticeL[®] Specification




2E/F CiTiceL[®]

Performance Characteristics

Nominal Range	0-200ppm
Maximum Overload	500ppm
Expected Operating Life	Two years in air
Output Signal	0.10 ± 0.02 µA/ppm
Inboard Filter	To remove SO ₂ and H ₂ S
Resolution	1ppm
Temperature Range	-20°C to +50°C
Pressure Range	Atmospheric ± 10%
Pressure Coefficient	No data
T₉₀ Response Time	≤40 seconds
Relative Humidity Range	15 to 90% non-condensing
Typical Baseline Range (pure air)	-1 to +3ppm equivalent
Maximum Zero Shift (+20°C to +40°C)	9ppm equivalent
Long Term Output Drift	<5% signal loss/year
Recommended Load Resistor	10 Ω
Bias Voltage	Not required
Repeatability	1% of signal
Output Linearity	Linear

N.B. All performance data is based on conditions at 20°C, 50%RH, and 1013mBar



Physical Characteristics

Weight	22g
Position Sensitivity	None
Storage Life	Six months in CTL container
Recommended Storage Temperature	0-20°C
Warranty Period	12 months from date of despatch




Distributed by:
 Shawcity Ltd
 91-92 Shrivenham Hundred Business Park
 Watchfield, Oxfordshire, SN6 8TY
 Tel: 01793 780622
 Email: sensororders@shawcity.co.uk
 www.shawcity.co.uk



Temperature Dependence

The output of a CiTiceL can vary with temperature. The graph here shows the variation in output with temperature for 2E/F CiTiceLs based on a sample of about 16 sensors. The results are shown in the graph as a mean for the batch, and expressed as a percentage of the signal at 20°C.

From a statistical viewpoint, for a sample of this size, the range in values observed for all sensors of this type will fall within a range three times the standard deviation above or below the mean. Assuming therefore this sample is typical, then the temperature behaviour of all 2E/F CiTiceLs will fall in the band +3SD to -3SD.



Cross-sensitivity Data

CiTiceLs may exhibit a response to certain gases in a sample other than the target gas. 2E/F CiTiceLs have been tested with a number of commonly cross-interfering gases and the results are given below. The table shows the typical response to be expected from a sensor when exposed to a given test gas concentration (relevant to safety, e.g. TLV levels).

<u>Gas</u>	<u>Conc.</u>	<u>2E/F</u>	<u>Gas</u>	<u>Conc.</u>	<u>2E/F</u>
Hydrogen sulphide:	15ppm	<1ppm	Hydrogen:	100ppm	<20ppm
Sulphur dioxide:	5ppm	0ppm	Hydrogen cyanide:	10ppm	0ppm
Nitric oxide:	35ppm	<±2ppm	Hydrogen chloride:	5ppm	0ppm
Nitrogen dioxide:	500ppm	5<x\$<25ppm	Ethylene:	100ppm	<50ppm
Chlorine:	1ppm	0ppm			

For details of other possible cross-interfering gases contact City Technology.

Ordering Information

The 2E/F Carbon Monoxide CiTiceL is supplied with side tags and tin-plated PCB pins.

Type 2E/F:- With side tag and PCB pin connections - 2E/F

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement City Technology Limited reserves the right to make product changes without notice. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale. The products are always subject to a programme of improvement and testing which may result in some changes in the characteristics quoted. As the products may be used by the client in circumstances beyond the knowledge and control of City Technology Limited, we cannot give any warranty as to the relevance of these particulars to an application. It is the clients' responsibility to carry out the necessary tests to determine the usefulness of the products and to ensure their safety of operation in a particular application.

Performance characteristics on this data sheet outline the performance of newly supplied sensors. Output signal can drift below the lower limit over time.