



3ME/F CiTiceL[®]

Standard mV Output CiTiceL[®]

Performance Characteristics

Sensor Type Used	3E/F
Expected Operating Life	Three years in air
Output Signal	1mV/ppm ($\pm 5\%$)
Maximum Range	0-2000ppm
Resolution	0.5ppm
Maximum Zero Output	0 \pm 1mV
Maximum Zero Shift (+20°C to +40°C)	3ppm equivalent
Temperature Range	-20°C to +50°C
Pressure Range	Atmospheric \pm 10%
Pressure Coefficient	0.02 %signal/mBar
T₉₀ Response Time	≤ 30 seconds
Relative Humidity Range	15 to 90% non-condensing
Long Term Output Drift	<5% of full signal/year
Repeatability	1% of signal
Output Linearity	Linear


N.B. All performance data is based on conditions at 20°C, 50%RH, and 1013mBar

Physical Characteristics

Weight	38g (with connector)
Position Sensitivity	None
Storage Life	Six months in CTL container
Recommended Storage Temperature	0-20°C
Warranty Period	12 months from date of despatch

Electrical Properties

Power Supply Required	7 to 18V d.c. single ended or ± 3.5 to ± 9 V d.c. dual
Power Consumption	250 μ A @ 9V d.c.
Calibration	Via built-in span and zero potentiometers






Temperature Dependence

The output of a CiTiceL can vary with temperature. The graph here shows the variation in output with temperature for 3E/F CiTiceLs based on a sample of about 16 sensors. The results are shown in the graph as a mean for the batch, and expressed as a percentage of the signal at 20°C.

From a statistical viewpoint, for a sample of this size, the range in values observed for all sensors of this type will fall within a range three times the standard deviation above or below the mean. Assuming therefore this sample is typical, then the temperature behaviour of all 3E/F CiTiceLs will fall in the band +3SD to -3SD.



Cross-sensitivity Data

CiTiceLs may exhibit a response to certain gases in a sample other than the target gas. 3E/F CiTiceLs have been tested with a number of common cross-interfering gases at concentrations relevant to safety applications (e.g. TLV levels). The concentrations used and typical response observed are given below.

Gas	Conc.	3E/F	Gas	Conc.	3E/F
Hydrogen sulphide:	15ppm	≈1ppm	Hydrogen:	100ppm	<60ppm
Sulphur dioxide:	5ppm	0ppm	Hydrogen cyanide:	10ppm	0ppm
Nitric oxide:	35ppm	<3.5ppm	Hydrogen chloride:	5ppm	0ppm
Nitrogen dioxide:	5ppm	0ppm	Ethylene:	100ppm	≤75ppm
Chlorine:	1ppm	0ppm	**For details of other possible cross-interfering gases contact City Technology.**		

Ordering Information

Standard mV CO CiTiceL MBE60-014

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement City Technology Limited reserves the right to make product changes without notice. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale. The products are always subject to a programme of improvement and testing which may result in some changes in the characteristics quoted. As the products may be used by the client in circumstances beyond the knowledge and control of City Technology Limited, we cannot give any warranty as to the relevance of these particulars to an application. It is the clients' responsibility to carry out the necessary tests to determine the usefulness of the products and to ensure their safety of operation in a particular application. Performance characteristics on this data sheet outline the performance of newly supplied sensors. Output signal can drift below the lower limit over time.



Distributed by:
Shawcity Ltd
91-92 Shrivenham Hundred Business Park
Watchfield, Oxfordshire, SN6 8TY
Tel: 01793 780622
Email: sensororders@shawcity.co.uk
www.shawcity.co.uk