



# 3MH mV Output CiTiceL<sup>®</sup>

## Performance Characteristics

<b>Sensor Type Used</b>	3H
<b>Expected Operating Life</b>	Two years in air
<b>Output Signal Standard</b>	1mV/ppm (±5%)
<b>High Output</b>	10mV/ppm (±5%)
<b>Maximum Range Standard</b>	0-250ppm
<b>High Output</b>	0-200ppm
<b>Resolution</b>	0.25ppm
<b>Maximum Zero Output</b>	0 ± 1mV
<b>Maximum Zero Shift (+20°C to +40°C)</b>	<2ppm equivalent
<b>Temperature Range</b>	-20°C to +50°C
<b>Pressure Range</b>	Atmospheric ± 10%
<b>Pressure Coefficient</b>	0.02% Signal/mBar
<b>T<sub>90</sub> Response Time</b>	≤35 seconds
<b>Relative Humidity Range</b>	15 to 90% non-condensing
<b>Long Term Output Drift</b>	<2% of full signal/month
<b>Repeatability</b>	1% of signal
<b>Output Linearity</b>	Linear


N.B. All performance data is based on conditions at 20°C, 50%RH, and 1013mBar

## Physical Characteristics

<b>Weight</b>	38g (with connector)
<b>Position Sensitivity</b>	None
<b>Storage Life</b>	Six months in CTL container
<b>Recommended Storage Temperature</b>	0-20°C
<b>Warranty Period</b>	12 months from date of despatch

## Electrical Properties

<b>Power Supply Required</b>	7 to 18V d.c. single ended or ± 3.5 to ± 9V d.c. dual
<b>Power Consumption</b>	250µA @ 9V d.c.
<b>Calibration</b>	Via built-in span and zero potentiometers






## Temperature Dependence

The output of a CiTiceL can vary with temperature. The graph here shows the variation in output with temperature for 3H CiTiceLs based on a sample of about 16 sensors. The results are shown in the graph as a mean for the batch, and expressed as a percentage of the signal at 20°C.

From a statistical viewpoint, for a sample of this size, the range in values observed for all sensors of this type will fall within a range three times the standard deviation above or below the mean. Assuming therefore this sample is typical, then the temperature behaviour of all 3H CiTiceLs will fall in the band +3SD to -3SD.

3H Temperature Coefficient Data



## Cross-sensitivity Data

CiTiceLs may exhibit a response to certain gases in a sample other than the target gas. 3H CiTiceLs have been tested with a number of commonly cross-interfering gases and the results are given below. The table shows the typical response to be expected from a sensor when exposed to a given test gas concentration (relevant to safety, e.g. TLV levels).

Gas	Conc.	3H	Gas	Conc.	3H
Carbon monoxide:	300ppm	≤6ppm	Hydrogen:	10,000ppm	<15ppm
Sulphur dioxide:	5ppm	<1ppm	Hydrogen cyanide:	10ppm	0ppm
Nitric oxide:	35ppm	<0ppm	Hydrogen chloride:	5ppm	0ppm
Nitrogen dioxide:	5ppm	≈1ppm	Ethylene:	100ppm	0ppm
Chlorine:	1ppm	≈0.1ppm			

\*\*For details of other possible cross-interfering gases contact City Technology.\*\*

## Ordering Information

Standard mV H<sub>2</sub>S CiTiceL..... MCH60-014  
 High Output mV H<sub>2</sub>S CiTiceL..... MCH60-024

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement City Technology Limited reserves the right to make product changes without notice. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale. The products are always subject to a programme of improvement and testing which may result in some changes in the characteristics quoted. As the products may be used by the client in circumstances beyond the knowledge and control of City Technology Limited, we cannot give any warranty as to the relevance of these particulars to an application. It is the clients' responsibility to carry out the necessary tests to determine the usefulness of the products and to ensure their safety of operation in a particular application. Performance characteristics on this data sheet outline the performance of newly supplied sensors. Output signal can drift below the lower limit over time.



**Distributed by:**  
 Shawcity Ltd  
 91-92 Shrivenham Hundred Business Park  
 Watchfield, Oxfordshire, SN6 8TY  
 Tel: 01793 780622  
 Email: sensororders@shawcity.co.uk  
 www.shawcity.co.uk