



MNO MediceLs[®]

Performance Characteristics

Output Signal	0.25 ± 0.05µA/ppm
Nominal Range	0-100ppm
Maximum Overload	1500ppm
Resolution at 20°C	0.5ppm
Expected Operating Life	One year
T₉₀ Response Time	<10 seconds
Output Linearity	Linear
Maximum Zero Shift (+20°C to +40°C)	2ppm equivalent
Operating Temp Range	-20°C to +50 °C
Typical Baseline Range (pure air)	-1 to +1ppm equivalent
Pressure	
Operating Range	800-1200mBar
Storage Range	800-1200mBar
Max Diff (capillary to amb.)	±100mBar
Relative Humidity Range	15% to 90% non-condensing
Typical Long Term Output Drift	Varies with usage levels
Bias Voltage	+300mV
Recommended Gain	1.1
Repeatability	2% of signal

Products

MNO-1	4-electrode NO MediceL
MNO-1B	MNO-1 with Bias Board
MNO-2	Compact 4-electrode NO MediceL
MNO-2B	MNO-2 with Bias Board


Physical Characteristics

Material	20% glass-filled polypropylene
Weight	21g (MNO-1), 16g (MNO-2)
Position Sensitivity	None
Storage Life	Six months in CTL container
Recommended Storage Temperature	0-20°C
Colour Coded Ring	Orange (MNO-1 only)
Warranty Period	12 months from date of despatch


MNO-1 / MNO-2 Cross Sensitivity Data


Gas	Response
Carbon monoxide (CO)	None
Nitrus oxide (N₂O)	None
Nitrogen dioxide (NO₂)	<25%
Halothane	None
Isoflurane	None
Desflurane	None

MNO-1 Nitric Oxide MediceL - Output vs Temperature
Gain set at 1.1



MNO-1 Nitric Oxide MediceL - Output vs Temperature
Gain set to 1.1





Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement City Technology Limited reserves the right to make product changes without notice. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale. The products are always subject to a programme of improvement and testing which may result in some changes in the characteristics quoted. As the products may be used by the client in circumstances beyond the knowledge and control of City Technology Limited, we cannot give any warranty as to the relevance of these particulars to an application. It is the clients' responsibility to carry out the necessary tests to determine the usefulness of the products and to ensure their safety of operation in a particular application.

Performance characteristics on this data sheet outline the performance of newly supplied sensors. Output signal can drift below the lower limit over time.